



L series motor performance data

STYLE	HP	MOTOR RPM				DRIVE RATIO	GEARBOX OUTPUT SHAFT RPM		GEARBOX OUTPUT SHAFT TORQUE		WEIGHT (kg/lbs)
		(460V)	(415V)	(380V)	(380V)		(460V)	(415V)	(460V)	(415V)	
L75-34	0.75	1720	1420	1420	50:1	34	28	157.3 Nm	172.3 Nm	157.8 Nm	25.0/55
L75-43	0.75	1720	1420	1420	40:1	43	35	124.4 Nm	137.8 Nm	126.2 Nm	25.0/55
L10-34	1.00	1720	1420	1420	50:1	34	28	210.6 Nm	229.5 Nm	210.2 Nm	28.0/62
L15-34	1.50	1720	1420	1420	50:1	34	28	314.6 Nm	344.6 Nm	315.5 Nm	27.7/61
L15-43	1.50	1720	1420	1420	40:1	43	35	248.7 Nm	275.7 Nm	252.4 Nm	27.7/61
L15-57	1.50	1720	1420	1420	30:1	57	47	187.6 Nm	205.3 Nm	188.0 Nm	25.0/55
L15-68	1.50	3440	2840	2840	50:1	68	57	157.3 Nm	169.3 Nm	155.0 Nm	26.8/59
L15-86	1.50	3440	2840	2840	40:1	86	71	124.4 Nm	135.9 Nm	124.4 Nm	26.8/59

Installation Size Performance Data

STYLE	A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	R	S
L75-34	14.37	3.850	9.91	15.63	0.937	0.377	9.882	1.00	9.06	0.453	5.02	5.000	4.750	3.386	5.984	0.531	6.000	6.358	7.25
L75-43	14.37	3.850	9.91	15.63	0.937	0.377	9.882	1.00	9.06	0.453	5.02	5.000	4.750	3.386	5.984	0.531	6.000	6.358	7.25
L10-34	13.70	3.882	9.91	18.48	0.941	0.382	9.803	1.00	8.35	0.433	4.960	5.000	3.429	5.827	0.531	6.000	6.358	7.25	7.25
L15-34	14.37	3.850	9.91	16.42	0.937	0.377	9.882	1.00	9.06	0.453	5.02	5.000	4.750	3.386	5.984	0.531	6.000	6.358	7.25
L15-43	14.37	3.850	9.91	16.42	0.937	0.377	9.882	1.00	9.06	0.453	5.02	5.000	4.750	3.386	5.984	0.531	6.000	6.358	7.25
L15-57	14.37	3.850	9.91	16.42	0.937	0.377	9.882	1.00	9.06	0.453	5.02	5.000	4.750	3.386	5.984	0.531	6.000	6.358	7.25
L15-68	14.37	3.850	9.91	15.63	0.937	0.377	9.882	1.00	9.06	0.453	5.02	5.000	4.750	3.386	5.984	0.531	6.000	6.358	7.25
L15-86	14.37	3.850	9.91	15.63	0.937	0.377	9.882	1.00	9.06	0.453	5.02	5.000	4.750	3.386	5.984	0.531	6.000	6.358	7.25

